

Element

Compound	Polyolefin	Polyester
	CP FILTER CP2 FILTER BM FILTER POROUSFINE(PP) CSW FILTER MINI FILTER	POROUSFINE(PET) CPH FILTER CHW FILTER LIC BAG FILTER
Acids		
Acetic acid(10%)	A	A
Sulfuric acid(50%)	A	A
Hydrochloric acid(10%)	A	A
Nitric acid(25%)	A	A
Phosphoric acid(25%)	A	A
Alkalis		
Sodium Hydroxide (5%)	A	A
Ammonia water(25%)	A	B
Alcohols		
Methanol	A	A
Ethanol	A	A
Isopropyl Alcohol	A	A
Hydrocarbons		
Hexane	B	B
Xylene	B	A
Toluene	B	A
Halogenated Hydrocarbons		
Carbon tetrachloride	C	B
Trichloroethylene	B	A
Miscellaneous		
Acetone	A	A
Methyl ethyl ketone	A	A
Methyl acetate	B	A
Ethyl acetate	B	A
Phenol	B	—
Formaldehyde	A	A
Kerosene	B	A
Brine	A	A
Hydrogen peroxide(10%)	A	A
Sodium hypochlorite(10%)	A	A

A : Compatible in most situations (20C°)

B : Prior testing is required

C : Not recommendable to use

Description of each characteristic data is based on our original test methods. The actual data may differ slightly from the data shown here by use conditions.